

## DX COILS

|                                                 |                                              |           |       |      |      |
|-------------------------------------------------|----------------------------------------------|-----------|-------|------|------|
| ROWS AVAILABLE                                  | 1                                            | 2         | 3     | 4    | 5    |
|                                                 | 6                                            | 8         | 10    | 12   |      |
| FPI AVAILABLE                                   | 6                                            | 7         | 8     | 9    | 10   |
|                                                 | 11                                           | 12        | 13    | 14   |      |
| TUBES OD & Wall Thickness<br><i>COPPER ONLY</i> | 5/8                                          | .020      | .025  | .035 | .049 |
|                                                 | 1/2                                          | .016 .020 |       |      |      |
|                                                 | 3/8                                          | .016      |       |      |      |
| FINS Material & Thickness                       | ALUM.                                        |           | .006  |      | .010 |
|                                                 | COPPER                                       |           | .006  |      |      |
| CASING                                          | 16 GA. GALV. STEEL<br>16 GA. STAINLESS STEEL |           |       |      |      |
| HEADERS<br><i>COPPER ONLY</i>                   | 5/8                                          | 7/8       | 1 1/8 |      |      |
|                                                 | 1 3/8                                        | 1 5/8     | 2 1/8 |      |      |
|                                                 | 2 5/8                                        | 3 1/8     |       |      |      |

| DIMENSIONAL DATA IN INCHES |     |      |     |     |     |     |    |                 |           |     |    |             |   |     |   | RETURN   |   | CONNECTION SIZES SWEAT |             |        |                                                                                                                                                                                                                           |  |  |
|----------------------------|-----|------|-----|-----|-----|-----|----|-----------------|-----------|-----|----|-------------|---|-----|---|----------|---|------------------------|-------------|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|
| ITEM                       | QTY | ROWS | FPI | SP1 | FH  | SP2 | CH | EP1             | FL        | EP2 | CL | MAX         | C | OAL | L | CD       | R | F                      | DISTRIBUTOR | RETURN | CU                                                                                                                                                                                                                        |  |  |
|                            |     |      |     |     |     |     |    |                 |           |     |    |             |   |     |   |          |   |                        |             |        |                                                                                                                                                                                                                           |  |  |
| P.O. #                     |     |      |     |     |     |     |    |                 | CUSTOMER  |     |    |             |   |     |   |          |   |                        |             |        | <div style="display: flex; align-items: center;"> <div> <p style="margin: 0; font-weight: bold; font-size: 1.2em;">PRECISION COILS</p> <p style="margin: 0; font-weight: normal;">Right Fit. Right Now.</p> </div> </div> |  |  |
| W.O. #                     |     |      |     |     |     |     |    |                 | MODEL NO. |     |    |             |   |     |   |          |   |                        |             |        |                                                                                                                                                                                                                           |  |  |
| APPROVED BY                |     |      |     |     |     |     |    |                 | TAG:      |     |    |             |   |     |   |          |   |                        |             |        |                                                                                                                                                                                                                           |  |  |
| DATE                       |     |      |     |     |     |     |    |                 | NOTES     |     |    |             |   |     |   |          |   |                        |             |        |                                                                                                                                                                                                                           |  |  |
| Performance Data           |     | CFM  |     |     | EAT |     |    | EVAPORATOR TEMP |           |     |    | REFRIGERANT |   |     |   | CAPACITY |   |                        |             |        |                                                                                                                                                                                                                           |  |  |